

- > Workplace
- > Retail
- > Aged Care
- > Living Rooms > Entrance
- > Bedroom
- > Rumpus > Kitchen
- > Bathrooms

Colours

Clean

1763



Fiordland

Rustic

1798

Riverton

1797

Foxton



1778 Longwood 1776

American Oak

1791

1793

Eden

London Fog



Victorian Oak



Helena Bay



Mercury Bay



Milford

The information given here is correct at the date of publication however due to Audacity Laminate's commitment to ongoing product improvement, Audacity Laminate reserves the right to modify this information without prior notice. Please note that Audacity Laminate's instructions regarding installation, cleaning and maintenance must be observed. Please refer to Jacobsen.co.nz for guidance. Whilst we have made every effort to ensure the colours and wood characteristics displayed are as accurate as possible these images may vary from the actual product.



Talk to one of our experts, or visit our website: 0800 800 460 | customer.services@jacobsen.co.nz | jacobsen.co.nz

Specifications

Range Name	Audacity Laminate	
Size (W x L)	235 x 1830 mm	
Thickness	10 mm	
M ² Per Box	2.15	
PCE per CTN	5	
Locking System	Angle-Snap	
Installation	Floating	
Surface	Waterproof	
Grading	AC4	
Bevel	Pressed Bevel UFH	
Environmental	FSC Certified	
Fire Resistance ISO 9239:1:2010	CHF > 1 kW/m2	
Emissions	ISO 16000	VOC B
VOC Emissions	California 01350	Compliant

Construction



Commercial Wear Layer for extra durability, scratch and stain resistance

Decorative Paper providing authentic wood look and feel

High Density Extra Stable Core 35% more stable than standard laminate

Edge Sealer protecting the core against moisture and humidity

Tight Lock Click System seals out moisture with 5x more contact points than standard laminate

NOTE: Silent Shield all-in-one moisture barrier and acoustic underlay is available for Jacobsen Audacity Laminate



Finishing Trims









Reducer











T Molding



