

Belle XL





Salt Lake Oak



Woodstock Oak



320 Husk Oak



350 Taylor Oak



500 Nordic Oak



Coastal Oak



540 Driftwood Oak



550 Desert Oak



Castlerock Oak



Sterling Oak



730 Misty Oak



790 Raven Oak

Specifications and colourations are subject to manufacturing tolerances. As part of the Godfrey Hirst continuous improvement program, Godfrey Hirst reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference. godfreyhirst.co.nz



Belle XL

Accentuate the grand space in a room with the ultimate in elegant style and affordability. Belle XL laminate planks are not only extra wide at 240mm, but each plank is an incredible 2050mm long, allowing you to create stunning interior style with a practical laminate floor.

Technical Data

Туре:	Laminate Flooring	Country of	Belgium
Dimensions:	2050mm x 240mm	Origin:	
Thickness:	8mm	Finish:	Soft Touch Matte
		Surface:	Embossed
Units Per Box:	7 boards		
m ² per box:	3.44	Substrate Laver:	850kg/m3 High Density Fibreboard
m ² per pallet:	113.652	Pooking Lover	Palanaing Lover
	4.0	Backing Layer:	Balancing Layer
Colours:	12	Profile:	Micro Bevel
		Installation	FitXpress®

Method:

Performance

Abrasion Rating:	(EN 13329) AC4	Light Reflectance	Available on Request
E3 Internal Moisture:	Wet Areas use - Kitchen, Powder Room, Integrated Laundry - E3/AS1 – 3.0 Watersplash – (Alternative Solution)^	Values:	
		Flammability:	(EN ISO 9239) CRF 6.1kW/m2
		Smoke Value:	(EN ISO 9239) 11% minutes
Swelling after submersion in water:	(EN 24336) ≤12%	Slip Resistance:	(AS 4586) P3
Impact Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet		
Light Fastness:	(EN ISO 105-B02) Class 8 - Blue Reference		

Sustainability

Product Transparency:	PEFC Chain of Custody certified.
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.
Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits



9001

















Micro Bevel Edge

Embossed

Matte Finish

Wear Resistant

Mid Range

All Godfrey Hirst Laminate floors must be installed in accordance with relevant New Zealand Standards and in conjunction with the Godfrey Hirst Laminate Flooring Installation Instructions. Warranty: All Godfrey Hirst floors carry a warranty supported by New Zealand after sales service. The Godfrey Hirst warranty is applicable to all Godfrey Hirst floors, sold in New Zealand. "As a New Zealand manufacturer, we endorse and recognise all rights of the consumer under the Consumer Guarantees Act 1993 (the "CGA") and further agree to match any performance guarantee or warranty offered in the market place, at the time of purchase, on any product which is equivalent to ours, where that performance guarantee or warranty offers influst to the consumer in addition to those under the CGA". For further information as to the warranty, installation, care and characteristic of this hard flooring please visit www.godfreyhirst.com or call 0800 500 210. "Subject to proper installation, maintenance and local budring ocde/regulatory approval. "Test results and certificates are available on request.

