



Suitable For Underfloor Heating



Quick & Easy Installation



Natural Look & Feel



PU Lacquer Dirt Resistant



R11* Slip Restraint



V-groove



Diamond Back



15 Year Residential Warranty



Class 23 Domestic Heavy



Class 32 Commercial Medium



REACH



A+

Construction	Heterogeneous Sheet Vinyl
Width	2.0m & 4.0m
Standard Roll Length	25m
Pattern Repeat	Refer to Vinyl Range Statement
Total Weight	1800g/m ²
Wearlayer Thickness	0.35mm
Total Thickness	2.6mm
Backing	Diamond Back
Surface Protection	PU / Natural Feel
Fire Rating	ISO 9239-1
Slip Resistance	DS-R11* (DIN 51130)
Acoustic Insulation	18dB (ISO 717)
Thermal Insulation	0.25W/mK
Indoor Air Quality	A+ Emissions
Underfloor Heating	Suitable
Chemicals Resistance	Very Good (EN ISO 26987)
Classification	Class 23 Domestic Heavy / Class 32 Commercial Medium
Warranty	15 Year Residential Warranty
Environmental	REACH Certificate of Compliance ISO 9001
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

* on selected items.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- **Rubber Migration:** Rubber migration (also known as Plasticiser Migration) is a condition that can cause vinyl to discolour. It is caused by rubber or latex products, eg rubber or latex-soled slippers, shoes and rubber backed mats, coming to contact with the vinyl over a constant period of time. It is neither a manufacturing nor an installation fault and therefore is not covered by our warranties.
- Plain, granite or patterned vinyls will either need to be reverse laid or a wider width should be used to allow for colour inequality, an additional allowance may have to be made for the pattern repeat.