## Crazy XL

## **Belgotex**<sup>®</sup>





Construction	Needlepunch carpet
Yarn	100% Stainproof Miracle Fibre
Width	2.0m, 3.0m & 4.0m
Standard Roll Length	40m
Yarn Weight	760g/m² / 22.5oz/yd²
Total Thickness	6.2mm
Backing	Resinbac
Electrical Properties	Antistatic
Fire Rating	CRF 5.7kW/m <sup>2</sup> (ISO 9239-1)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
UV Fade Resistance	5000 hours UV stabilised fibre.
Use	Indoor
Rating	Commercial
Stair Rating	Suitable
Warranty	5 Year Needlepunch Warranty
Environmental	Low VOC, solution dying uses no water. Meets all PRODIS-GUT requirements.
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. It is recommended that the carpet be adhered directly to the subfloor, which should be clean, dry and level. All adjacent pieces must be laid running in the same direction. Must be laid in accordance with AS/NZ Installation Standards.

■ For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz

• Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.

