## **DIGITAL EVOLUTION**

## **Belgotex**<sup>®</sup>





















| Construction                    | Heterogeneous Sheet Vinyl   |  |
|---------------------------------|---|--|
| Width                           | 4.0m  |  |
| Standard Roll Length            | ±22m  |  |
| Pattern Repeat                  | Design: 3D Abstract Coral Reef Flatweave Herringbone Galaxy Grass Jungle Riverstone Treadplate Water Absolute Concrete Black Stud Checker Board Malthouse Brick Marble  | Pattern Repeat: 4000mm x 4000mm 4000mm x 4000mm 500mm x 1000mm 4000mm x 4000mm 2000mm x 2000mm 2000mm x 2000mm 666mm x 1000mm 1000mm x 1000mm 1500mm x 4000mm 2000mm x 5000mm 570mm x 570mm 4000mm x 570mm 4000mm x 3200mm |
| Total Weight                    | 2800g/m²  |  |
| Wearlayer Thickness             | 0.70mm  |  |
| Total Thickness                 | 2.0mm   |  |
| Surface Protection              | PU Lacquer  |  |
| Slip Resistance                 | R10 (DIN 51130)   |  |
| Electrical Propensity           | <2kV (EN 1815)  |  |
| Fire Rating                     | Bfl -s1 (EN 13501)  |  |
| Acoustic Insulation             | ΔLw 6dB (ISO 717/2)   |  |
| Dynamic Coefficient of Friction | >0.6 (EN 13893)   |  |
| Wear Group                      | T (EN 660-2)  |  |
| Dimensional Stability           | ≤0.40% (EN ISO 23999, EN 434)   |  |
| Curling                         | ≤8mm (EN ISO 23999)   |  |
| Thermal Resistance              | 0.014m²K/w (ISO 8302)   |  |
| Thermal Insulation              | 0.14W/m/K (EN 12524)  |  |
| Residual Indentation            | ≤0.20mm (EN ISO 24343-1, EN 433)  |  |
| Indoor Air Quality              | FloorScore®, A+ Emissions   |  |
| Chemical Resistance             | Resistant (EN ISO 26987, EN 423)  |  |
| Light Fastness                  | ≥6 (EN ISO 105B02)  |  |
| Underfloor Heating              | Suitable  |  |
| Classifications                 | Class 34 Commercial Very Heavy / Class 43 Industrial Heavy  |  |
| Warranties                      | 10 Year Commercial Warranty   |  |
| Environmental                   | 100% Phthalate Free, 100% Recyclable<br>ISO 14001, ISO 9001   |  |
| Installation                    | Please contact Gilt Edge Industries for all adhesive and installation instructions.<br>NB: If recommended adhesive is not used, claims will not be accepted.<br>Must be laid in accordance with AS/NZ Installation Standards. |  |

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- Rubber Migration: Rubber migration (also known as Plasticiser Migration) is a condition that can cause vinyl to discolour. It is caused by rubber or latex products, eg rubber or latex-soled slippers, shoes and rubber backed mats, coming to contact with the vinyl over a constant period of time. It is neither a manufacturing nor an installation fault and therefore is not covered by our warranties.
- Plain, granite or patterned vinyls will either need to be reverse laid or a wider width should be used to allow for colour inequality, an additional allowance may have to be made for the pattern repeat.

