



Construction	Tufted Cut Pile Carpet
Yarn	100% Solution Dyed Nylon
Width	4.0m
Standard Roll Length	35m
Yarn Weight	1200g/m ² / 36oz/yd ²
Total Weight	2310g/m ²
Total Thickness	10.7mm
Machine Gauge	1/8th
Primary Backing	Woven Polypropylene
Secondary Backing	Cosyback
Electrical Properties	Antistatic
Electrical Propensity	≤ 2kV
Fire Rating	ISO 9239-1
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Underfloor Heating	Suitable
Rating	Extra Heavy Duty Residential
Stair Rating	Suitable
Warranties	15 Year General Warranty 15 Year Residential Wear Warranty 15 Year Stain Resistant Warranty 15 Year Fade Resistant Warranty 15 Year Colourfast Warranty 5 Year Manufacturing Defects Warranty 3 Year Commercial Wear Warranty
Environmental	GUT Label GreenStar, Homestar™, Well Building Standard® Environmental Product Declaration Low VOC, solution dying uses no water ISO 14001
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.