Ingrain



TECHNICAL SPECIFICATIONS

Country of Origin:	Australia
Colours:	8 Standard
Yarn:	100% Statron Solution Dyed Nylon
Surface Texture:	Textured Loop Pile
Gauge:	47.2/10cm (1/12th Gauge)
Product Thickness:	7.00mm
B.1. 3.7.1.1.	

Backing:	Enviro Bac®
Carpet Tiles & Planks Size:	250mm x 1000mm
Installation Method:	Direct Stick
Type:	Carpet Tiles and Planks
Units Per Box:	16.00
m² per box:	4

Pile Weight: 745g/m²

PERFORMANCE

Anti-Static: (AATCC 134) <3.5KV at 21°C & 20% Relative Humidity

Flammability: CRF 6.4kW/m2 (Direct Stick)~
Colourfast to light: (ISO 105-B-02-1994) 6-7
Light Reflectance: Available on Request
Stain Resistance: Stain Warden®

Biocontaminant Control: Bioshield® Antimicrobial Control
ACCS Rating: Contract Extra Heavy Duty - 4 Star

Contract Warranty: GH Commercial provides comprehensive warranties for our products. All warranties are

issued on a project by project basis. Please contact us to discuss your requirements

further.

Smoke Value: 143% minutes (Direct Stick)

SUSTAINABILITY

PVC Minimisation: PVC Free

Indoor Air Quality: Green Building Council Compliant for VOC emission rate limits

Green Star: Environmental Certification Scheme (ECS). Level 4 Maximum Points - Certificate #17119

Accreditation: Manufactured under a quality, environmental and health and safety system certified and

Manufactured under a quality, environmental and health and safety system certified and complying with ISO 9001, ISO 14001 and ISO 45001 by accredited certification bodies.



















Ingrain





Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All GH Commercial carpet tiles and planks must be installed in accordance with AS2455 Parts 1 & 2 (latest version) and the GH Commercial Carpet Tile/Plank Installation Instructions.

Chair pads are recommended under office chairs with roller castors to preserve appearance retention, act as a deterrent toward delamination and to prevent premature or accelerated wear. Walk-off tiles from the Tuff Stuff II Collection are recommended at entryways to reduce soiling. ~Test results and certificates are available on request.

*Guarantee is in addition to any rights consumers may have under Australian consumer laws.

Terms and conditions apply - for full information in respect to the scope of the guarantee please contact your GH Commercial Account Manager or our Head Office.