

Malvern



110
Valetta



180
Greystone



290
Ashlyn



310
Avonlea



320
Kensington



330
Sheffield



340
Sherwood



500
Scotswood



520
Whitstone




700
Whitecliffs



710
Rockwood



720
Longridge




730
Keystone



740
Brentwood




750
Coleridge



760
Braemar

Specifications and colourations are subject to manufacturing tolerances. As part of the Godfrey Hirst continuous improvement program, Godfrey Hirst reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.
godfreyhirst.co.nz

Malvern



770
Ashworth



780
Riversleigh



790
Orwell

Malvern

Malvern brings together high design interior styles combined with an extremely durable wear layer. Malvern's heavy duty residential rating dictates confidence with a floor that will handle the very busiest of home environments combined with an easy clean waterproof surface. Its super compact backing gives the product premium strength and wear resistance.

Technical Data

Type:	Vinyl Sheet Flooring	Country of Origin:	Belgium
Thickness:	2.2mm	Finish:	Matte
Wear Layer:	0.4mm	Top Layer:	Natural Feel
Roll Width:	2m	Coating System:	HyperGuard+®
Pattern Repeat:	Please refer to swatch images	Installation Method:	Direct Stick
Colours:	19		

Performance

Dimensional Stability:	(ISO 23999) norm ≤ 0,40%	Light Fastness:	(ISO 105-B02) 6-7
Thermal Conductivity:	(EN ISO 10456 / EN ISO 12664) 0,25 W/ (m.K) / 0,0195 (m2.K/W)	Smoke Value:	EN ISO 9239: 111% min
Classification:	(EN ISO 10874) 23, 32	Slip Resistance:	AS4586:2013: SRV 40 : P3
Abrasion Rating:	(ISO 10582) Type I	Castor Chair:	(EN ISO 4918) Very good
E3 Internal Moisture:	All wet areas - E3/AS1 (Acceptable Solution)^	Residual Indentation:	(EN ISO 24343-1) 0,13 (Norm 0,20 mm)
Impact Sound Reduction:	(EN ISO 717-2) ΔLw 13 dB		

Sustainability

Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.
Indoor Air Quality:	LOW VOC



Waterproof Surface^



ISO 9001



ISO 14001



Affordable



European Made