

EXPONA® superplank

Expona Superplank is a conceptually developed collection of Luxury Vinyl Tiles designed to inspire engaging and stylish spaces. Carefully curated by a team of Australian interior design experts, the range of beautifully authentic wood planks and abstract geometric tile designs can be laid solo for simplicity, or in conjunction with one another to create truly unique interiors.



	Gauge	EN 428/EN ISO 24346	2.0mm
	Wear Layer	EN 429/EN ISO 24340	0.55mm
	Plank Size	EN 427/EN ISO 24342	18 @ 152.4 x 1219.2 = 3.34m ² 15 @ 184.2 x 1219.2 = 3.37m ² 14 @ 203.2 x 1219.2 = 3.46m ² 18 @ 304.8 x 609.6 = 3.34m ²
	Total Weight	EN 430/EN ISO 23997	2964g/m ²
	General Performance	EN 649 EN ISO 10582	Conforms Conforms
	Use Area	EN 685/EN ISO 10874	
	Reaction to Fire	AS ISO 9239.1	>8kW/m ²
	Abrasion Resistance	EN 660-2	Group T
	Binder Content	EN ISO 10582	Type I
	Slip Resistance	EN 13893 DIN 51130 AS/NZS 4586	Class DS (dry condition) R10 R10 For safety flooring with sustainable wet slip resistance, refer to Expona Control or the Polysafe ranges.
	Indentation Residual	EN 433/EN ISO 24343-1	≤ 0.1mm
	Dimensional Stability	EN 434/EN ISO 23999	≤ 0.25% max
	Thermal Conductivity	EN 12524	0.25W m/K.
	Light Fastness	ISO 105-B02	(Method 3) ≥6
	Castor Chair (continuous use)	EN 425/ISO 4918	Suitable
	Electrical Behaviour (body voltage)	EN 1815	≤2kV Classified as 'antistatic'
	VOC Emissions	Indoor Air Comfort GOLD AgBB VOC test	Eurofins certified product Very low emissions
	Responsible Sourcing	SA 8000	Approved factory
<p>Environmentally Preferable Flooring - Expona Superplank PUR is GreenTag LCA Rate certified with GreenRate A - Gold Plus. Generic EN 15804 Environmental Product Declaration (EPD) is available on request. It is 100% recyclable and contains up to 40% recycled material. Visit www.polyflor.com/sustainability</p>			
<p>PUR - Expona Superplank PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low cost, polish-free maintenance regime for the lifetime of the flooring.</p>			
	<p>For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, consult your local Polyflor representative or contact us directly on 1800 777 425 or sales@polyflor.com.au The data presented is correct at the time of printing. For latest information, please visit our website polyflor.com.au Decoration and shade may vary slightly from the samples shown.</p>		

