

Regent 1200



105
Emmet



180
Longreach



300
Brokenhill



350
Cobar



380
Birdsville



545
Georgetown



550
Melrose



555
Charleville



560
Burke



700
Silverton



740
Winton



790
Stamford

Regent 1200

Durable, easy to maintain and water resistant[^], Regent vinyl planks are the perfect choice for creating a beautiful timber look throughout all areas of your home. The stunning colour palette provides a range of options to suit a variety of interiors, so you can find a warm and comfortable timber-look floor that complements your style. Available in two sizes, Regent 1200 is a shorter plank. All colours in this range are also available in the longer and thicker Regent 1500 range.

Direct stick vinyl plank for a professional looking installation

Technical Data

Type:	Vinyl Plank Flooring	Colours:	12
Dimensions:	1219mm x 178mm	Country of Origin:	South Korea
Thickness:	2.5mm	Finish:	Matte
Wear Layer:	0.5mm	Surface:	Embossed
Units Per Box:	18 boards	Profile:	Square Edge
m² per box:	3.91	Coating System:	PUR
m² per pallet:	215.05	Installation Method:	Direct Stick

Performance

Dimensional Stability:	(ISO 23999) Length: 0.20%, Width: 0.05%, Curling 0.00%	Light Fastness:	(EN ISO 105-B02) 6-7
Thermal Conductivity:	TBA	Light Reflectance Values:	105 - 42.44 180 - 11.05 300 22.14 350 - 13.58 380 - 13.05 545 - 19.96 550 - 14.12 555 - 16.23 560 - 19.50 700 - 39.08 740 - 25.84 790 -13.49
Abrasion Rating:	(EN 660-2) Group T	Flammability:	(EN ISO 9239) CRF 8.1kW/m ²
E3 Internal Moisture:	All wet areas - E3/AS1 – 3.0 Watersplash – (Alternative Solution) [^]	Smoke Value:	Direct Stick: (EN ISO 9239) 135% minutes With Underlay: (EN ISO 9239) 179% minutes
Impact Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet	Slip Resistance:	(AS 4586) P2, R9

Sustainability

Product Transparency:	Global Green Tag, GreenRate Level A certified, Best Environmental Practice PVC certified product
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.
Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits



All Godfrey Hirst Vinyl Plank floors must be installed in accordance with relevant New Zealand Standards and in conjunction with the Godfrey Hirst Vinyl Plank Flooring Installation Instructions. Warranty: All Godfrey Hirst floors carry a warranty supported by New Zealand after sales service. The Godfrey Hirst warranty is applicable to all Godfrey Hirst floors, sold in New Zealand. *As a New Zealand manufacturer, we endorse and recognise all rights of the consumer under the Consumer Guarantees Act 1993 (the "CGA") and further agree to match any performance guarantee or warranty offered in the market place, at the time of purchase, on any product which is equivalent to ours, where that performance guarantee or warranty offers rights to the consumer in addition to those under the CGA. For further information as to the warranty, installation, care and characteristic of this hard flooring please visit www.godfreyhirst.com or call 0800 500 210. ~Test results and certificates are available on request. ^Subject to proper installation, maintenance and local building code/regulatory approval.

Regent 1200

Colour Variation Best
Environmental
Practice PVC